

CLAIM AMENDMENTS

I claim:

1. (currently amended) A ~~device~~ support system for supporting a body or a portion thereof, comprising:

a foam mattress, cushion, seating pad or ~~other~~ similar support structure[[,]] containing ~~cutout portions or otherwise designed or~~ a plurality of vacant regions[[,]] and configured to reduce local stresses on a supported body, reduce cross contamination between a patient and ~~the~~ a patient surroundings, and reduce the incidence of dust mites into ~~the~~ said support system;

a bladder or membrane impervious to gases or other fluids, completely encasing said mattress, cushion, seating pad or ~~other~~ similar support structure;

a passageway or ~~other~~ means[[,]] to allow and control the ingress and egress of a gas or other fluid into or out of ~~the pores and/or~~ said vacant regions, within or around the ~~materials~~ support structure encased by said bladder or membrane; and

~~optionally~~, a pressure/vacuum pump to allow continuous variation of the fluid pressure within said bladder or membrane.

2. (currently amended) A ~~device~~ support system according to claim 1 wherein the ~~encased material~~ support structure ~~comprises~~ is a foam mattress in which portions of the support ~~material~~ structure have been removed or omitted in one or more selected regions of the material, forming empty regions [[,]] and the ~~sides of the opening thus formed~~ empty regions are ~~such that they slope outward and downward from the center like a truncated cone or a bell-shaped~~ opening region.

3. (currently amended) A ~~device~~ support system according to claim 1 wherein one or more of the edges of the mattress, cushion, seating pad or other body support surface is undercut such that the edge tapers inward toward the bottom of the mattress, cushion, seating pad or body support element.
4. (currently amended) A ~~device~~ support system according to claim 1 wherein said mattress, cushion, or seating pad is formed from a convoluted foam material.
5. (currently amended) A ~~device~~ support system as in claim 1 wherein said mattress, cushion, or seating pad is formed from a convoluted foam material and said convoluted foam material is inserted with smooth side upward and one or more cut-outs are made for the purpose of reducing local stresses on the body or sections thereof.
6. (currently amended) A ~~device~~ support system according to claim 1 wherein the ~~encased material~~ support structure provides for reduction of localized stresses by a modular construction technique using different types of foam material in selected regions to form a composite foam mattress.
7. (currently amended) A ~~device~~ support system according to claim 1 wherein the ~~encased material~~ support structure provides for reduction of localized stresses by a modular construction technique using different types of foam material encased in individual membranes in selected regions to form a composite foam mattress.
8. (currently amended) A ~~device~~ support system according to claim 1 wherein said bladder

is permanently sealed to prevent any escape or replacement of the fluid contained therein.

9. (currently amended) A ~~device~~ support system according to claim 1 wherein said bladder is enclosed by a Ziploc⁷ or similar fastening means.

10. (currently amended) A device according to claim 1 wherein the ~~encased material~~ support structure comprises a seat cushion and wherein said seat cushion contains provisions for localized relief of stress comprising one or more regions where material has been removed or omitted selectively from said seat cushion.

11. (currently amended) A ~~device~~ support system as in claim 1 where a variable orifice is contained within the ~~surrounding~~ encasing membrane to control the rate of gaseous exchange from within the membrane to outside of the membrane and vice versa.

12. A ~~device~~ support system for supporting a body or a portion thereof, comprising:

a foam mattress, cushion, seating pad or ~~other~~ similar support structure[.], containing ~~cutout portions or otherwise designed or~~ a plurality of vacant regions[.] and configured to reduce local stresses on a supported body, reduce cross contamination between a patient and ~~the~~ a patient surroundings, and reduce the incidence of dust mites into ~~the~~ said support system;

a bladder or membrane[.], permeable or semi-permeable to gases or other fluids, completely encasing said mattress, cushion, seating pad or ~~other~~ similar support structure;

a passageway or ~~other~~ means[.], to allow and control the ingress and egress of a gas or other fluid into or out of ~~the pores and/or~~ said vacant regions, within or around the ~~materials~~ support structure encased by said bladder or membrane; and

~~optionally, a pressure/vacuum pump to allow continuous variation of the fluid pressure within said bladder or membrane.~~

13. (withdrawn) A method for reducing the possibility of development of deleterious body lesions in a human body under conditions of continued bed confinement by;

placing a mattress, cushion, seating pad or ~~other~~ similar support structure, designed or configured to minimize localized stress concentrations caused by the weight of the body thereon, within a bladder or membrane impervious to gases or other fluids,

completely encasing said mattress, cushion, seating pad or ~~other~~ similar support structure,

varying the fluid pressure in the ~~material~~ support structure as a means of controlling the resiliency of said ~~material~~ support structure to the desired support level.

14. (currently amended) A method for reducing the possibility of development of deleterious body lesions in a human body under conditions of continued bed confinement by;

placing a mattress, cushion, seating pad or other similar support structure, designed or configured to minimize localized stress concentrations caused by the weight of the body thereon, within a bladder or membrane impervious to gases or other fluids,

completely encasing said mattress, cushion, seating pad or other similar support structure,

varying the fluid pressure in the material support structure as a means of controlling

the resiliency of said material support structure to the desired support level,
wherein the ~~encased-material~~ support structure comprises a mattress containing
provision for reduction of localized stresses in certain portions of the body being
supported by the removal of portions of the mattress material in one or more
selected regions.

15. (currently amended) A A method for reducing the possibility of development of
deleterious body lesions in a human body under conditions of continued bed confinement
by:

placing a mattress, cushion, seating pad or other similar support structure, designed
or configured to minimize localized stress concentrations caused by the
weight of the body thereon, within a bladder or membrane impervious to
gases or other fluids,

completely encasing said mattress, cushion, seating pad or other similar support
structure,

varying the fluid pressure in the material support structure as a means of controlling
the resiliency of said material support structure to the desired support level,
wherein the ~~encased-material~~ support structure contains provisions for reduction of
localized stresses by the removal of portions of the ~~mattress-material~~ support
structure in one or more selected regions~~[[,]]~~ forming a plurality of vacant regions,
where ~~the hole in the remaining material is~~ said vacant regions are in the shape of
an upright truncated cone.

16. (currently amended) A method for reducing the possibility of development of

deleterious body lesions in a human body under conditions of continued bed confinement

by:

placing a mattress, cushion, seating pad or other similar support structure, designed or configured to minimize localized stress concentrations caused by the weight of the body thereon, within a bladder or membrane impervious to gases or other fluids,

completely encasing said mattress, cushion, seating pad or other similar support structure,

varying the fluid pressure in the material support structure as a means of controlling the resiliency of said material support structure to the desired support level,
wherein the ~~encased material~~ support structure contains provisions for reduction of localized stresses by means of cutting or slicing portions of the mattress material in one or more selected regions.

17. (withdrawn) A method according to claim 13 wherein the ~~encased material~~ support structure comprises a seat cushion of suitable support material.

18. (currently amended) A method for reducing the possibility of development of deleterious body lesions in a human body under conditions of continued bed confinement

by:

placing a mattress, cushion, seating pad or other similar support structure, designed or configured to minimize localized stress concentrations caused by the weight of the body thereon, within a bladder or membrane impervious to gases or other fluids,

completely encasing said mattress, cushion, seating pad or other similar support structure.

varying the fluid pressure in the material support structure as a means of controlling the resiliency of said material support structure to the desired support level,

wherein the ~~encased material~~ support structure comprises a seat cushion and said seat cushion contains provisions for localized relief of stress comprising one or more regions where material has been removed selectively from the seat cushion.

19. (currently amended) A method for reducing the possibility of development of deleterious body lesions in a human body under conditions of continued bed confinement by:

placing a mattress, cushion, seating pad or other similar support structure, designed or configured to minimize localized stress concentrations caused by the weight of the body thereon, within a bladder or membrane impervious to gases or other fluids,

completely encasing said mattress, cushion, seating pad or other similar support structure.

varying the fluid pressure in the material support structure as a means of controlling the resiliency of said material support structure to the desired support level,

wherein one or more of the edges of the mattress, cushion, or seating pad is undercut such that the edge tapers inward toward the bottom of the mattress, cushion, or seating pad.

20. (withdrawn) A method according to claim 13 wherein said mattress, cushion, or seating

pad comprises a plurality of modules, separated from one another and contained within individual fluid-tight membranes or bladders.

21. (currently amended) A method for reducing the possibility of development of deleterious body lesions in a human body under conditions of continued bed confinement
by:

placing a mattress, cushion, seating pad or other similar support structure, designed or configured to minimize localized stress concentrations caused by the weight of the body thereon, within a bladder or membrane impervious to gases or other fluids,

completely encasing said mattress, cushion, seating pad or other similar support structure,

varying the fluid pressure in the material support structure as a means of controlling the resiliency of said material support structure to the desired support level,

wherein said mattress, cushion, or seating pad is formed from a convoluted foam material.

22. (withdrawn) A method according to claim 13 wherein the encased material comprises a seat cushion.

23. (currently amended) A method for reducing the possibility of development of deleterious body lesions in a human body under conditions of continued bed confinement
by:

placing a mattress, cushion, seating pad or other similar support structure, designed

or configured to minimize localized stress concentrations caused by the weight of the body thereon, within a bladder or membrane impervious to gases or other fluids.

completely encasing said mattress, cushion, seating pad or other similar support structure.

varying the fluid pressure in the material support structure as a means of controlling the resiliency of said material support structure to the desired support level,

wherein the ~~encased material~~ support structure comprises a seat cushion and wherein said seat cushion contains provisions for localized relief of stress comprising one or more regions where material has been removed or omitted selectively from said seat cushion.

24. (new) The support system of claim 12 further comprising a pressure/vacuum pump to allow continuous variation of the fluid pressure within said bladder or membrane.

25. (new) The support system of claim 12 wherein said bladder or membrane is enclosed by a Ziploc or similar fastening means.

Respectfully submitted,

A handwritten signature in cursive script, reading "Robert L. Greeson". The signature is written in black ink and is positioned above a horizontal line.

Robert L. Greeson
Registration No. 52,966
900 Washington Ave.
P.O. Box 1470
Waco, TX 76703-1470
(254) 755-4221
(254) 754-6331 (Fax)
greeson@namanhowell.com



CERTIFICATE OF
MAILING

I hereby certify that this correspondence is being deposited with the United States Postal Service as First Class Mail in an envelope addressed to: MAIL STOP NON-FEE AMENDMENT, COMMISSIONER FOR PATENTS, P.O. Box 1450, Alexandria, VA 22313-1450, on this the 25th day of June, 2004

April Chase
April Chase